


CRISTALFLEX



PRIMJENA

MATERIJAL CIJEVI:

OJAČANJE:

TEMPERATURA:

usis i tlak pitke vode, mlijeka, vina, voćnih sokova i drugih prehrambenih tekućina
 prozirni atoksični plastificirani PVC bez ftalata
 tvrdi PVC žute boje otporan na gaženje
 -10 +60 °C

Promjer (mm)	Radni tlak (bar)	Rasprs. tlak (bar)	Podtlak (bar)	Težina (kg/m)	Pol. sav. (mm)	Kolut (m)	Montaža			
							Obujmice			
20	7	21	0.7	0.230	70	50	18	23 - 25	Inox	-
25	7	21	0.7	0.280	110	50	20	29 - 31	Inox	
30	7	21	0.7	0.350	140	50	20	32 - 35	Inox	
32	7	21	0.7	0.370	150	50	20	36 - 39	Inox	
35	7	21	0.7	0.425	160	50	20	40 - 43	Inox	
38	6	18	0.6	0.450	170	50	22	44 - 47	Inox	
40	6	18	0.6	0.510	180	50	22	48 - 51	Inox	
45	6	18	0.6	0.640	200	50	22	52 - 55	Inox	
51	6	18	0.6	0.760	230	50	22	56 - 59	Inox	
55	6	18	0.6	0.860	310	25	22	60 - 63	Inox	BAND-IT
60	5	15	0.5	0.900	280	50	22	64 - 67	Inox	
63	5	15	0.5	0.970	300	50	23	68 - 73	Inox	
70	5	15	0.4	1.120	310	50	23	74 - 79	Inox	
76	5	15	0.4	1.270	340	50	23	80 - 85	Inox	
80	5	15	0.3	1.450	350	30	23	86 - 91	Inox	
90	3	9	0.4	1.850	450	30	23	98 - 103	Inox	
102	3	9	0.4	2.200	500	30	23	113 - 121	Inox	
110	3	9	0.3	2.500	550	30	23	122 - 130	Inox	
120	3	9	0.3	2.800	700	20	23	131 - 139	Inox	
127	3	9	0.3	3.200	750	20	23	140 - 148	Inox	
152	2	6	0.3	4.300	850	20	23	149 - 161	Inox	
200	2	6	0.3	6.500	1000	10	26	188 - 200	Inox	
250	1.5	4.5	0.3	8.500	1800	*	-			
300	1	3	0.3	11.000	2000	*	-			

BAND-IT